

SAFETY DATA SHEET (SDS)

Product: POLIMIN LP-22 Mattlatex

1. Identification

Product name: POLIMIN LP-22 Mattlatex

Manufacturer: POLIMIN USA

Recommended use: Interior wall & ceiling latex paint

2. Hazard Identification

This product is not classified as hazardous under OSHA Hazard Communication Standard (29 CFR 1910.1200).

GHS Classification: Not hazardous

Label elements: None

3. Composition/Information on Ingredients

Water-based acrylic latex emulsion with titanium dioxide, fillers, and additives.

Approximate composition: Water 30–40%, Acrylic polymer 20–40%, TiO₂ 10–20%, additives <5%.

4. First Aid Measures

Inhalation: Move to fresh air.

Eye contact: Rinse with water for several minutes.

Skin contact: Wash with soap and water.

Ingestion: Rinse mouth, do not induce vomiting. Seek medical advice if symptoms persist.

5. Fire-Fighting Measures

Suitable extinguishing media: Water spray, foam, CO₂, dry powder.

Hazards: Non-flammable (water-based).

6. Accidental Release Measures

Contain spill with absorbent material. Collect for disposal.

Prevent entry into drains or waterways.

7. Handling and Storage

Keep containers tightly closed.

Store at +5...+30 °C (41–86 °F).

Protect from freezing.

8. Exposure Controls / Personal Protection

No special protection required.

Recommended: safety glasses, protective gloves during prolonged use.

9. Physical and Chemical Properties

Appearance: Liquid paint

Density: ~1.5 kg/L (~12.5 lb/gal)

VOC: <30 g/L (<0.25 lb/gal)

pH: 8–9

Drying time: 2–3 h (recoat), 28 days full cure

10. Stability and Reactivity

Stable under normal conditions.

Avoid freezing and extreme heat.

11. Toxicological Information

Non-toxic. Not classified as hazardous.
Low VOC content.

12. Ecological Information

Water-based product. Biodegradable components.
Avoid uncontrolled release into environment.

13. Disposal Considerations

Dispose in accordance with local regulations.
Do not pour into drains.

14. Transport Information

Not regulated as dangerous goods (DOT, IATA, IMDG).

15. Regulatory Information

Complies with OSHA Hazard Communication Standard.
VOC <30 g/L.

16. Other Information

Date of preparation: 2025-09-03
This SDS is provided for guidance and compliance purposes.